

## Paraffin dispenser



Compact device for dispensing molten paraffin on demand directly from its tap.  
Digital display for temperature setting and display.

- **Capacity : 7.5 l**
- **Ambient temperature setting +5 °C to 70 °C**
- **Stainless steel cuvette with antimicrobial coating**
- **Heated tap to prevent wax clogs**
- **Compact model**

Temperature (°C)	Amb +5 °C to 70 °C
Display resolution (°C)	1
Accuracy	+/- 1 °C
Cuvette capacity (l)	7.5
Weight (kg)	7
Dimensions W x D x H (mm)	181 x 500 x 455
Power consumption (W)	480
Power supply	230 V, 50-60 Hz
<b>Cat. No.</b>	<b>002125</b>
<b>€ Excl. VAT</b>	<b>NC -</b>

## Manual rotation microtome



- **For making tissue sections in paraffin**
- **Ergonomic, easy-to-handle handwheel with mechanism lock**
- **Cutting surface 50 x 45 mm**
- **Sample clamp and universal clamp for cassette easily interchangeable and swivelling**
- **Advanced macro system**
- **Supplied with 2 slide holders for high and low profile disposable slides, with tiltable finger guard**

Cutting thickness (µm)	0.5 - 60
Cutting thickness adjustment	From 0.5-2 µm in 0.5 µm intervals From 2-10 µm in 1 µm intervals From 10-20 µm in 2 µm intervals From 20-60 µm in 5 µm intervals
Angle of slide orientation	0 - 12 °
Horizontal displacement of the sample (mm)	35
Vertical displacement of the sample (mm)	46
Sample Orientation	8° (x-y eyes); 360° gyratory
Dimensions L x D x H (mm)	300 x 570 x 270
Weight (kg)	34
Power supply	220 V - 50 Hz
<b>Cat. No.</b>	<b>942836</b>
<b>€ Excl. VAT</b>	<b>NC -</b>

## Sterile polystyrene Pasteur pipettes



- **In transparent polystyrene, length 150 mm and 230 mm**
- **Advantages over glass pipettes: safer, more economical, gamma sterility guaranteed**
- **In individual packaging or 25 units**

Length (mm)	Ind. sterile packaging	Packed per 25, sterile
152	<b>978357</b>	<b>978358</b>
229	<b>978359</b>	<b>978360</b>
<b>Units/bag</b>	50	25
<b>Units/carton</b>	200	500
<b>€ Excl. VAT/carton</b>	<b>NC -</b>	<b>NC -</b>

ANALYSIS AND MEASUREMENTS