

Folding probe thermometer



- ▶ Special food industry, HACCP and EN 13485 compliant
- ▶ IP65 waterproof enclosure (water jet)
- ▶ Stainless steel penetration probe, rotatable by 180°
- ▶ Automatic switch-off
- ▶ Zero point calibration function

Temperature	- 40 °C to + 150 °C
Accuracy	+/- 0,5 °C from - 20 °C to + 140 °C, +/- 1 °C from - 40 °C to - 20 °C
Resolution	0.1 °C
Dimensions (mm)	116 x 38 x 20
Weight (g)	40
Probe dimensions Ø x W (mm)	3,2 - 2,6 x 60
Batteries	CR 2032
Cat. No.	253749
€ Excl. VAT	NC -

Accessory

Cat.No.	Description	€ Excl. VAT
045322	Battery for Thermometer 253749	NC -

Checktemp and Checktemp 1 precision thermometers



- ▶ Measurement accuracy ± 0.2 °C from -20 to 90 °C
- ▶ CAL CHECK function at start-up to check the internal calibration and measurement accuracy of the instrument
- ▶ EN 13485 compliant
- ▶ Compact design case
- ▶ Silicone cable for prolonged use in negative cold and high temperatures (052028B)
- ▶ 106 mm fixed probe in food grade AISI 316 stainless steel
- ▶ Can be used in an atmosphere of -20 to 50°C
- ▶ Water resistance IP 65
- ▶ HACCP applications
- ▶ Auto power off (after 8 or 60 minutes or disabled)
- ▶ Delivered with battery and holder

Model	Checktemp	Checktemp 1
Range	-50 to 150°C	-50 to 150°C
Accuracy	$\pm 0,2$ °C (-20 to 90 °C) / $\pm 0,5$ °C (outside)	
Probe	L = 106 mm, Ø 3,6 mm	L = 97.3 mm, Ø 3,5 mm with 1 m cable
Battery	1 x 3V type CR 2032 Li-ion	3 x 1,5 V AAA
Dimensions / Weight	70.4 x 50.5 x 22 mm / 51.3 g	107 x 59 x 16.5 mm / 80 g

Cat.No.	Description	€ Excl. VAT
052028B	Checktemp pocket thermometer with fixed probe	NC -
052026B	Checktemp 1 pocket thermometer with probe and 1 m cable	NC -

Temperature indicator, magnetic fixing



- ▶ For continuous temperature monitoring of cold rooms, freezers and refrigerators
- ▶ Stainless steel food grade thermistor probe and 1 metre silicone cable for easy cleaning
- ▶ Cal-Check function to check the accuracy of the instrument
- ▶ Error message "ERR" to indicate the need to replace the battery
- ▶ Easy installation by magnet
- ▶ Large LCD display

Range	-50 to +150°C
Resolution	0.1 °C
Accuracy	+/- 0,3 °C (-20 to +90 °C) ; +/- 0,5 (outside)
Calibration	Factory only
Calibration test	By switch on the front panel
Probe	40 x 5 mm stainless steel with 1 mm food grade cable
Battery	1 x 1.5 V AAA / 3 year life span
Environment	0 to +50 °C; RH 95%
Dim. / Weight	93 x 39 x 31 mm / 60 g
Cat. No.	052393
€ Excl. VAT	NC -

Checktemp 4® Precision Thermometer



- ▶ Equipped with a folding probe
- ▶ Designed for laboratory and food industry applications
- ▶ Switching on by opening the probe and activating the automatic calibration status test
- ▶ Supplied with 1.5 V AA battery

Range	-50 to +220 °C (environment 0 to 50 °C / max. humidity 95 %)
Resolution	0.1°C (-50 to 199.9°C); 1°C (200 to 220°C)
Accuracy	+/- 0.3 °C +/- 1 character (-20 to 90 °C); +/- 1 % F.S. +/- 1 character (external)
Probe	Stainless steel, with penetration tip, Ø x W : 3.5 x 117 mm
Dim. / Weight	165 x 50 x 20 mm / 100 g
Cat. No.	052388B
€ Excl. VAT	NC -