






















## ClearLine® screw cap microtubes without seal

	Standard					
						
Volume (ml)	0.5	1.5	2	0.5	1.5	2
Out diameter (mm)	10.20					
Inner diameter (mm)	8.5					
Height (mm)	46.2	46.2	46.2	47.5	47	47.8
Material	Virgin polypropylene; medical grade					
Sterile	Yes					
Autoclavable	Yes					
Max centrifugal speed (g)	25000					
Skirt	No	No	No	Yes	Yes	Yes
Graduation	No	Yes	Yes	No	Yes	Yes
Marking area	No	Yes	Yes	No	Yes	Yes
Operating temperature	-85 °C to +121 °C					
Specifications	USP Class VI compliant; DNase, RNase and endotoxin free; CE IVD mark					
<b>Units/box</b>	2 bags with 500 microtubes					
<b>Cat. No. natural</b>	<b>390418CL</b>	<b>390420CL</b>	<b>390422CL</b>	<b>390419CL</b>	<b>390421CL</b>	<b>390423CL</b>
<b>€ Excl. VAT/box</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>

	For insert					
						
Volume (ml)	0.5	1.5	2	0.5	1.5	2
Out diameter (mm)	10.20					
Inner diameter (mm)	8.5					
Height (mm)	48.8	48.2	48.4	49.2	49	49.8
Material	Virgin polypropylene; medical grade					
Sterile	Yes					
Autoclavable	Yes					
Max centrifugal speed (g)	25000					
Skirt	No	No	No	Yes	Yes	Yes
Graduation	No	Yes	Yes	No	Yes	Yes
Marking area	No	Yes	Yes	No	Yes	Yes
Operating temperature	-85 °C to +121 °C					
Specifications	USP Class VI compliant; DNase, RNase and endotoxin free; CE IVD mark					
<b>Units/box</b>	2 bags with 500 microtubes					
<b>Cat. No. natural</b>	<b>390424CL</b>	<b>390426CL</b>	<b>390428CL</b>	<b>390425CL</b>	<b>390427CL</b>	<b>390429CL</b>
<b>€ Excl. VAT/box</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>

	For insert with clip					
						
Volume (ml)	0.5	1.5	2	0.5	1.5	2
Out diameter (mm)	10.20					
Inner diameter (mm)	8.5					
Height (mm)	48.8	48.2	48.4	49.2	49	49.8
Material	Virgin polypropylene; medical grade					
Sterile	Yes					
Autoclavable	Yes					
Max centrifugal speed (g)	25000					
Skirt	No	No	No	Yes	Yes	Yes
Graduation	No	Yes	Yes	No	Yes	Yes
Marking area	No	Yes	Yes	No	Yes	Yes
Operating temperature	-85 °C to +121 °C					
Specifications	USP Class VI compliant; DNase, RNase and endotoxin free; CE IVD mark					
<b>Units/box</b>	2 bags with 500 microtubes					
<b>Cat. No. natural</b>	<b>390430CL</b>	<b>390432CL</b>	<b>390434CL</b>	<b>390431CL</b>	<b>390433CL</b>	<b>390435CL</b>
<b>€ Excl. VAT/box</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>	<b>NC -</b>