## 15 AND 50 ML CENTRIFUGE TUBES

	L	abcon Pe	rform™ aı	nd Perfor	mR™ Tub	es, skirte	d		
	PerformR™ Tubes						PerformR™ tubes, skirted		
							Oitilititi 1		
Volume (ml)	15			50			50		
Diameter (mm)	1			29			30		
Height (mm)	118			115			115		
Material	Polypropylene tube; HDPE cap			Polypropylene tube; HDPE cap			Polypropylene tube; HDPE cap		
Sterile	Yes	No	Yes	Yes	No	Yes	No	Yes	No
Cap Type	Screw-ir	; flat with elast	omer seal	Screw-in	; flat with elasto	omer seal	Screw-in	; flat with elast	omer seal
Autoclavable	Yes			Yes			Yes		
Max centrifugal speed (g)	12500			12500			10500		
Skirt	No			No			Yes		
Graduation	Yes standard and inverted; maximum level			Yes standard and inverted; maximum level			Yes (2.5 ml increments from 5 to 45 ml)		
	indication for freezing			indication for freezing					
Marking area	Yes on tube and cap			Yes on tube and cap			Yes		
Colour	Translucent			Translucent			Translucent		
Operating temperature	-80 °C to +121 °C			-80 °C to +121 °C			-80 °C to +121 °C		
Specifications Units/box	Free of DNases, RNases, endotoxins (c 0,05 EU/ ml) and ATP; certified low metal content (c 1 ppm); CE IVD; according to IATA 95 kPa for transport of infectious agents; U.S.P Class VI compliant; recyclable Bag of 500 Bag of 500 tubes lubes and bag polypropylene			Free of DNases, RNases, endotoxins (< 0,05 EU/ ml) and ATP; certified low metal content (< 1 ppm); CE IVD; according to IATA 95 kPa for transport of infectious agents; U.S.P Class VI compliant; recyclable Bag of 500 Bag of 500 12 tubes and bag polypropylene			Free of DNases, RNases, endotoxins (< 0,05 EU/ ml) and ATP; certified low metal content (< 1 ppm); CE IVD; according to IATA 95 kPa for transport of infectious agents; U.S.P Class VI compliant; recyclable  10 bags of 50		
C . N . G .		of 500 caps	racks of 25 tubes		of 500 caps	racks of 25 tubes			of 500 caps
Cat. No. flat green cap	949434	949901	949536	949432	949917	949538 NC -	949026	949027	949028
€ Excl. VAT/box	NC -	NC-	NC -				NC - NC - NC -		
Сар Туре	Screw; with thick joint area; reinforced seal			Screw; with thick joint area; reinforced seal			Screw; with thick joint area; reinforced seal		
Specifications	Free of DNases, RNases, endotoxins (c 0,05 EU/ ml)and ATP; certified low metal content (c 1 ppm); CE IVD; according to U.S.P Class VI; recyclable			Free of DNases, RNases, endotoxins (< 0,05 EU/ ml)and ATP; certified low metal content (< 1 ppm); CE IVD; according to U.S.P Class VI; recyclable			Free of DNases, RNases, endotoxins (c 0,05 EU/ ml)and ATP; certified low metal content (c 1 ppm); CE IVD; according to U.S.P Class VI; recyclable		
Units/box	Bag of 500 tubes	Bag of 500	polypropylene racks of 25 tubes	Bag of 500 tubes	Bag of 500	polypropylene racks of 25 tubes		10 bags of 50 tubes	
Green cap with reinforced seal	949024	949902	949537	949020	949918	949539	949029	949030	949031
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -