

# LARGE VOLUME THREADED TUBES

## Nalgene™ Polycarbonate Tubes

Thermo  
SCIENTIFIC

NALGENE



Volume (ml)	175	250				500		1000		
Diameter (mm)	61.4	61.9	61.8	61.8	69.5	69.5	97.6	98.1	-	
Height (mm)	144.3	145.8	127.6	134.4	169.6	160	188.4	180.2	-	
Material	Polycarbonate; polypropylene cap								Polycarbonate; Polypropylene cap, modified PPE closure	
Sterile	No									
Bottom	Conical	Rounded	Flat	Flat	Flat	Flat	Flat	Flat	Flat	
Autoclavable	Yes									
Max centrifugal speed (g)	27500	27500	27500	27500	13500	13700	7100	7100	15810	
Graduation	Yes	No	No	No	No	No	No	No	No	
Marking area	No									
Specifications	Silicone seal cap for better sealing and reinforced closure	Waterproof	-	Reinforced silicone seal	-	Reinforced silicone seal	-	-	Silicone seal; designed for Fiberlite rotors (FCS 6X1000Y, F8S 6X1000Y, F9S 4X1000Y); non-cytotoxic	
Units/box	4 tubes	4 tubes	4 tubes	4 tubes	4 tubes	4 tubes	4 tubes	4 tubes	6 tubes	
Natural cap	<b>029259</b>	<b>029244</b>	<b>029241</b>	<b>029206</b>	<b>029242</b>	<b>029255</b>	<b>029200</b>	<b>029243</b>	-	
Blue cap	-	-	-	-	-	-	-	-	<b>029906</b>	
€ Excl. VAT/carton	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	NC -	

### Adapters

Cat. No.	Description	Units/box	€ Excl. VAT/box
<b>029274</b>	Adapter for Cat. No. 029259	4	NC -
<b>029273</b>	Adapter for Cat. No. 029244	4	NC -



## Nalgene™ PTFE and low density polyethylene tubes

Thermo  
SCIENTIFIC

NALGENE

Volume (ml)	250	
Diameter (mm)	60	61.2
Height (mm)	128.8	131.9
Material	PTFE FEP ; ETFE cap	HDPE; polypropylene cap
Sterile	No	
Bottom	Flat	
Autoclavable	Yes	No
Max centrifugal speed (g)	4000	8000
Graduation	No	
Marking area	No	
Operating temperature	- 100 °C to +150 °C	- 100 °C to +120 °C
Specifications	Excellent chemical resistance	
Units/box	1 tube individually packed	Bag of 6 tubes
Cat. No. natural	<b>029245</b>	<b>029240</b>
€ Excl. VAT/box	NC -	NC -

