

# POLYPROPYLENE TUBES, STRAIGHT NECK

CORNING

## Corning® Gosselin™ Polypropylene threaded tubes, straight neck



Volume (ml)	2	3-5		5	10	
Out diameter (mm)	10.9	12	12	12.8	15.4	15.4
Inner diameter (mm)	8.9	10	10	10.9	13.5	13.5
Height (mm)	42.5	75	75	74.5	95	95
Material	Polypropylene					
Sterile	No	No	Yes	Yes	No	Yes
Bottom	Rounded					
Caps	No	No	Yes	Yes	No	Yes
Cap Type	-	-	Winged cap	Winged cap	-	Winged cap
Autoclavable	Yes					
Max centrifugal speed (g)	3000					
Skirt	No					
Graduation	No					
Marking area	No					
Colour	Transparent	Translucent	Translucent	Translucent	Translucent	Translucent
Operating temperature	-20 °C to +120 °C					
Units/box	4 bags of 1500 tubes	5 bags of 500 tubes	4 bags of 625 tubes	4 bags of 500 tubes	5 bags of 250 tubes	4 bags of 250 tubes
Cat. No. tube only	<b>080044</b>	<b>080073</b>	-	-	<b>080031</b>	-
Cat. No. red cap	-	-	<b>080075</b>	<b>080072</b>	-	<b>080084</b>
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -

## Greiner Bio-One Polypropylene tubes, straight neck

greiner  
BIO-ONE



Volume (ml)	4	5	12	14
Out diameter (mm)	11.8	12	16.1	18
Inner diameter (mm)	10.1	10	13.5	15
Height (mm)	54.7	74.2	98.9	95
Material	Polypropylene			
Sterile	No			
Bottom	Rounded			
Caps	No			
Autoclavable	Yes			
Max centrifugal speed (g)	5800	5800	5800	4800
Skirt	No			
Graduation	No			
Marking area	No			
Colour	Translucent			
Operating temperature	-196 °C to +120 °C			
Units/box	15 bags of 240 tubes	8 bags of 250 tubes	Bag of 1600 tubes	Bag of 1500 tubes
Cat. No. tube only	<b>112201</b>	<b>115201</b>	<b>160201</b>	<b>187201</b>
€ Excl. VAT/box	NC -	NC -	NC -	NC -