

TPX volumetric flasks

PMP class A volumetric flasks



- ▶ Transparent, with polypropylene R.I.N. cap
- ▶ Individually adjusted circle marking
- ▶ Tolerances in accordance with the requirements for category A according to DIN EN ISO 1042
- ▶ With printed batch number and certificate
- ▶ Autoclave up to +121 °C, cleaning not exceeding 60 °C

Cat. No.	Volume (ml)	Tolerance +/- (ml)	Height (mm)	RIN cap	Units/box	€/box
o68682	10	0.04	90	10 / 19	6	NC -
o68683	25	0.04	115	10 / 19	6	NC -
o68684	50	0.06	150	10 / 19	6	NC -
o68685	100	0.10	180	14 / 23	6	NC -
o68686	250	0.15	235	19 / 26	5	NC -
o68687	500	0.25	270	19 / 26	4	NC -
o68688	1000	0.40	310	24 / 29	3	NC -



Azlon® TPX volumetric flasks



- ▶ Autoclavable with unscrewed cap)
- ▶ Class B
- ▶ Ground neck
- ▶ In translucent polypropylene or transparent TPX
- ▶ With polypropylene cap and gauge line

Volume (ml)	CN neck	ø x H* (mm)	Cat. No.	€
25	10/19	40 x 118	001073	NC -
50	14/23	48 x 156	001074	NC -
100	14/23	63 x 180	001075	NC -
250	19/26	83 x 240	001076	NC -
500	19/26	103 x 270	001077	NC -
1000	24/29	125 x 310	093001	NC -

* total height with cap

Decanting ampoules



Teflon Nalgene™ Teflon Separating funnels



- ▶ Made of Teflon FEP, Teflon TFE shut-off valve, Tefzel ETFE screw cap, phthalate-free
- ▶ Unbreakable, transparent and non-stick bulbs for easy cleaning
- ▶ Non-wetting
- ▶ Leak-proof plug and stopcock, easily removable valve assembly for cleaning
- ▶ Can be used with mechanical stirrers if a clamp is installed where the stopcock is inserted to tighten the hose
- ▶ Autoclavable except for the stopcock assembly, which can be chemically disinfected

Cat. No.	Volume (ml)	Cap size (mm)	Stem length under stopcock (mm)	Units/bag	Units/box	€/box
o29659	125	28	65	1	4	NC -
o29737	250	33	65	1	1	NC -
o29738	500	43	65	1	1	NC -
o29739	1000	53	65	1	1	NC -
o29740	2000	53	65	1	1	NC -