

Platinum silicone tubing

- Platinum treated silicone tubing - length 25 m
- Ultra-smooth inner surface
- Thermal resistance : -60 °C to +200 °C
- Hardness: 60 Shore A
- Certified Animal Free

- Supplied with certificate of conformity
- Manufactured in a class 10,000 (ISO 7) clean room, on an ISO9001 and ISO13485 certified site
- Complies with : USP class VI, European Pharmacopoeia, CFR 177.2600, USP 661, USP 381, ISO 10993 (-4,5,10,11)

Cat. No.	Inn. Ø x out. Ø (mm)	Thickness (mm)	€ the 25 m roll
351053	0.8 x 4.0	1.6	NC -
351054	1.6 x 4.8	1.6	NC -
351055	3.0 x 7.0	2.0	NC -
351056	3.2 x 6.4	1.6	NC -
351057	4.8 x 8.0	1.6	NC -
351059	4.8 x 9.5	2.4	NC -
351060	6.0 x 12.0	3.0	NC -
351061	6.4 x 9.5	1.6	NC -
351062	6.4 x 11.2	2.4	NC -
351064	8.0 x 12.8	2.4	NC -
351065	8.0 x 16.0	4.0	NC -
351066	9.7 x 14.5	2.4	NC -
351067	12.7 x 19.1	3.2	NC -
351068	15.9 x 22.3	3.2	NC -



Versilic silicone tubing

Cat. No.	Inn. Ø x out. Ø (mm)	Long. (m)	€	Cat. No.	Inn. Ø x out. Ø (mm)	Long. (m)	€ the roll
260000	0.5 x 2.5	50	NC -	260023	7 x 11	25	NC -
260001	1 x 3	50	NC -	225232	7 x 12	25	NC -
260002	1.5 x 3	50	NC -	225233	7 x 13	25	NC -
260003	2 x 4	50	NC -	260026	8 x 11	25	NC -
260004	2 x 5.5	50	NC -	673412	8 x 12	25	NC -
260005	2 x 6	50	NC -	260028	8 x 14	25	NC -
260006	3 x 5	50	NC -	225397	8 x 16	25	NC -
260007	3 x 5.5	50	NC -	260030	8.5 x 12	25	NC -
225223	3 x 6	50	NC -	260031	9 x 13	25	NC -
260009	3 x 7	50	NC -	374021	10 x 14	25	NC -
225224	4 x 6	50	NC -	374022	10 x 16	25	NC -
260011	4 x 7	25	NC -	225399	10 x 18	25	NC -
225227	4 x 8	25	NC -	260035	10 x 23	25	NC -
260013	4 x 10	25	NC -	260036	12 x 15.5	25	NC -
260014	5 x 7	25	NC -	260037	12 x 17	25	NC -
260015B	5 x 8	25	NC -	260038	15 x 21	25	NC -
260016	5 x 9	25	NC -	260039	18 x 24	10	NC -
225228	5 x 10	25	NC -	260040	20 x 27	10	NC -
260018	6 x 8	25	NC -	260041	25 x 35	10	NC -
260019B	6 x 9	25	NC -	260042	30 x 40	10	NC -
673411	6 x 10	25	NC -	260043	40 x 50	10	NC -
260021B	6 x 12	25	NC -	260044	50 x 60	10	NC -
225231	7 x 10	25	NC -	-	-	-	-



- Silicone peroxide
- Temperature resistant from -50 °C to +200 °C
- Autoclavable
- ISO 10993
- USP Class VI compliant
- Recommended for the transfer of liquids where neutrality is required

Silclear® Silicone tubing

- Medical grade, delivered with certificate of conformity
- Hardness : 58
- Operating temperature from -60 to +220 °C

Cat. No.	Inn. Ø x out. Ø (mm)	Roll of	€ the roll
910601	2 x 4	25 m	NC -
910603	4.8 x 9.5	15 m	NC -
910604	6.4 x 9.5	15 m	NC -
910605	6.4 x 12.7	15 m	NC -
910606	12.7 x 19.05	15 m	NC -

