

Tygon 2375 and 2475 tubing



- Resistant to the most aggressive chemicals
- Plasticizer-free, which reduces the risk of contamination of the fluid
- Exceptionally smooth inner surface prevents the deposition of particles
- Temperature resistant from - 78 °C to + 52 °C
- Low sorption preserves fluid integrity
- Density : 0.29 - Hardness Shore: 72 - Transparent
- Complies with USP class VI criteria

Models 2375				Models 2475			
Cat. No.	Inn. ø x out. ø (mm)	Long. (m)	€ the roll	Cat. No.	Inn. ø x out. ø (mm)	Long. (m)	€ the roll
110608B	1.6 x 3.2	15	NC -	261013	1,6 x 4,8	15	NC -
110609B	1.6 x 4.8	15	NC -	261014	3.2 x 6.4	15	NC -
110610B	2.4 x 4	15	NC -	261015	4.8 x 8	15	NC -
110611B	3.2 x 6.4	15	NC -	260470	6.4 x 9.6	15	NC -
110612B	4 x 5.6	15	NC -	261016	8 x 11.2	15	NC -
110613B	4.8 x 8	15	NC -	261017	9.6 x 12.7	15	NC -
110615B	8 x 11.2	15	NC -	261018	12.7 x 19.1	15	NC -
110616B	9.5 x 12.7	15	NC -	261019	15.9 x 22.3	15	NC -
110617B	12.7 x 19.1	15	NC -	-	-	-	-
110618B	15.9 x 22.3	15	NC -	-	-	-	-
110619B	19 x 25.4	15	NC -	-	-	-	-

- **Models 2375**
- Complies with the European Directive 2002/95/EC (RoHS)
- New DEHP-free formulation
- **Models 2475**
- NSF and FDA compliant for food contact
- Low protein absorption

Tygon Chemical tubing



- Long life on peristaltic pump
- Plasticizer-free inner core
- Excellent chemical resistance
- Resistant to absorption and adsorption of aqueous products
- Good resistance to chemical disinfectants
- Density : 0.98 - Hardness ShoreA : 61 - Beige
- Temperature resistant from - 60 °C to + 74 °C
- Complies with FDA criteria for food contact
- Complies with the European Directive 2002/95/EC (RoHS)

Cat. No.	inner ø x outer ø (mm)	Length (m)	€ the roll
110636	3.2 x 6.4	15	NC -
110637	4.8 x 8	15	NC -
110638	6.4 x 9.6	15	NC -
110639	9.5 x 12.7	15	NC -
110640	12.7 x 19.1	15	NC -

Versilon 2001 tubing



- Good bending strength
- Outstanding chemical resistance
- Do not contain plasticizers
- Temperature resistant from - 78 °C to + 52 °C
- FDA compliant for food contact
- Density : 0.88 - Hardness ShoreA : 69 - Transparent
- Complies with the European Directive 2002/95/EC (RoHS)

Cat. No.	inner ø x outer ø (mm)	Length (m)	€ the roll
110628	1.6 x 4.8	15	NC -
110629	3.2 x 6.4	15	NC -
110630	4.8 x 8	15	NC -
110631	6.4 x 9.6	15	NC -
110632	8 x 11.2	15	NC -
110633	9.5 x 12.7	15	NC -
110634	12.7 x 19.1	15	NC -
110635	25.4 x 35	15	NC -

Stainless Steel Filling Countersunk for pipe



- To connect to the end of the pipe to keep it immersed
- 304 stainless steel, autoclavable

Cat. No.	Tube Inn Ø (mm)	€
129355	0.8	NC -
129356	1.6	NC -
129357	2.4	NC -
129358	3.1	NC -
129359	4.8	NC -
129360	6.4	NC -

Stainless steel dispensing tips



- 304 stainless steel, autoclavable
- To be connected to the end of the pipe to dispense the liquid

Cat. No.	Tube Inn Ø (mm)	€
129349	0.8	NC -
129350	1.6	NC -
129351	2.4	NC -
129352	3.1	NC -
129353	4.8	NC -
129354	6.4	NC -