

V-LINE fire resistant cabinet 90 min

- Reduced width cabinet, only 45 cm thanks to the drawer: space-saving, optimal storage capacity almost identical to conventional cabinets with 90 cm wide doors
- Tall cabinet with 1 vertical drawer
- Motor-assisted drawer opening and automatic closing after 60 seconds
- Overview of the stored products with easy access from the right or left side of the drawer
- Key lock of the drawer
- Ventilation holes DN75 for connection to a filter or self-contained ventilation system
- Equipped with 4 or 5 shelves, 1 grating and 1 retention tray 11-litre to the floor
- Colour: anthracite grey body and drawer colour to be chosen or unicolour model in grey or white
- Fire resistant for 90 minutes according to EN 14470-1
- Ext. Dimensions W x D x H (mm) 450 x 863 x 1966



Model Unicolour white

Drawer colour	Model with 1 vertical drawer 4 shelves		Model with 1 vertical drawer 5 shelves	
	Cat. No.	€	Cat. No.	€
Yellow	571207	NC -	571212	NC -
Grey	571208	NC -	571213	NC -
Red	571209	NC -	571214	NC -
Blue	571210	NC -	571215	NC -
Silver	571211	NC -	571216	NC -
Cabinet, unicolour : grey	-	-	571218	NC -
Cabinet, unicolour : white	571219	NC -	571220	NC -

Accessory

Cat. No.	Description	€
571235	Safety rails for 1 shelf	NC -

Enter the Cat. No. on dulis.nl to find the selection guide for safety cabinets.



Combined cabinet with 90 min fire resistance NF EN 14470-1

- Two separate inner compartments for storing flammable liquids and chemicals in one cabinet
- Door holding system included
- Security lock with interchangeable barrel
- Shelves adjustable in height in 32 mm increments
- Permissible distributed load per shelf : 75 kg
- Connection Ø 75 mm for ventilation system on top of the enclosure (strongly recommended, see page 1308)
- Certified to NF EN 14470-1



Model	K90.196.120.MF.FWAS	
Ext. Dim. W x D x H (mm)	1197 x 617 x 1969	
Int. Dim. W x D x H (mm)	1050 x 524 x 1742	
Weight (kg)	515	
Left compartment (flammable liquids)	3 shelves Gratings Floor retention tray 22.5 l	3 shelves Gratings Floor retention tray 22.5 l
Right compartment (Acids and bases)	4 shelf trays without metal Plastic tray	6 shelf trays without metal Plastic tray
Cat. No.	571002C	571049B
€	NC -	NC -

Refrigerated safety cabinet UB-S-90

- Under-bench cabinet with refrigeration system for keeping products in a refrigerated environment
- Fire resistance 90 min EN 14470-1
- Ventilation system with activated carbon filter for retention of solvent vapours
- Pull-out drawer with lock and stainless steel drip tray; ergonomic: remains open (regardless of opening)
- Load capacity 50 kg
- Maximum refrigeration capacity : 2 °C
- Ext. dim. W x D x H: 1108 x 574 x 630 mm / Dim. int. W x D x H: 980 x 450 x 500 mm
- Weight : 180 kg



Cat. No.	Description	€
571122	Refrigerated safety cabinet UB-S-90	NC -

The safety cabinets are delivered carriage paid to the quay. For delivery on the first floor, please consult us.

