

Weighing table



Weighing table designed to absorb shocks and oscillations that could distort measurement results.

- Polished granite plate (34 kg) as an integrated work surface, supported on absorbent rubber elements
- Work table with aluminium profile frame and height adjustable legs
- Dimensions
 - L x D x H table: 770 x 650 x 815 mm
 - L x D x H tray: 400 x 450 x 70 mm

Cat. No.	Description	€
0151006B	Weighing table	N/A -

Mini glove box



- Acrylic chamber (PMMA)
- Temperature resistant from -20 °C to +70 °C
- Rubber feet
- Side openings for gloves
- Lightweight, easily transportable

Ext. Dimensions W x H x D (mm)	300 x 400 x 400
Int. Dimensions W x H x D (mm)	290 x 390 x 390
Volume (l)	34
Weight (kg)	5.7
Max. load (kg)	10
Opening for gloves (mm)	190
Cat. No.	499108
€	N/A -

Glove boxes



- For safe and contamination-free sample handling
- Panels made of clear acrylic (PMMA); light and rigid aluminium frame (total weight 14 kg); base panel made of PE
- Temperature resistant from -20 °C to +70 °C
- Hermetic
- Gas filling connector with self-closing valve
- Ext. dim. / int. W x H x D: 890 x 700 x 600 mm / 850 x 500 x 540 mm
- Max. load approx. 40 kg
- Supplied with quick connection, olive and size 9 gloves
- **Optional: 2-door airlock for sample introduction**
- Capable of holding a 1000 ml bottle
- Safety system to prevent simultaneous opening of both doors
- Ext. dim. / int. W x H x D: 320 x 330 x 260 mm / 220 x 275 x 320 mm

Gloves for glove box

- Ambidextrous gloves
- Suitable for 190 mm diameter opening
- Length 750 mm
- Made of natural rubber, antistatic
- Tear, puncture and abrasion resistant



Size	7	8	9	€ the pair
Cat. No.	490943	490944	490945	N/A -

Cat. No.	Description	€
490942	Glove boxes	N/A -
490941	Glove box + airlock	N/A -

Gas regulator for glove box



- Regulates the gas inlet to the glove box to reduce gas consumption
- Supplied with sensor, tubing to connect the flow meter to the measuring instrument and power cable
- Power supply: 230 V / 50 Hz

Humidity range	0 - 50 % rF / rH
Temperature range	-20 °C to 60 °C
Display range	0.1 - 99 %, -30 °C to 70 °C
Precision sensor	0.1 rF/rH, 0.1 °C
Gas flow meter (l/min)	2-10
Sensor length (m)	1.2
Weight (kg)	1.8
Cat. No.	499109
€	N/A -