


## LID Tasklight

- Robust and quiet flexible arm lamps for precise and durable positioning
- LEDs on printed circuit guaranteeing a long life (50000h) or halogen bulb (5000h) depending on the model
- Standard switch, contactless or with dimmer depending on model

- Compliant with standards EN 60 601-1/-2-41 and EN 60 598-2-25
- Class 1 medical device
- Lamp only, to be completed with a stand
- Made in France
- 3 year warranty



### Carla LED lamp ➤ Swivel head ➤ Diffused lighting 25°

Flexible arm (mm)	650	1000	1230
Luminous intensity (lm)	420		
Illumination at 50cm (lx)	7000		
Illuminated area at 50cm (mm)	200		
Colour temperature	4500°K (neutral white)		
Colour rendering index	IRC 95/100		
Power consumption	4.2 W		
Head dimensions (mm)	60 x 100		
<b>With standard switch</b>	<b>013417</b>	<b>013419</b>	<b>013421</b>
€	N/A -	N/A -	N/A -
<b>With contactless switch</b>	<b>013418</b>	<b>013420</b>	<b>013422</b>
€	N/A -	N/A -	N/A -

### Tina Halogen Lamp ➤ Swivel head ➤ Precise 10° lighting

Flexible arm (mm)	650	1140
Luminous intensity (lm)	300	
Illumination at 50cm (lx)	23000	
Illuminated area at 50cm (mm)	100	
Colour temperature	3000°K (warm white)	
Colour rendering index	IRC 100/100	
Power consumption	20 W	
Head dimensions (mm)	70 x 70	
<b>With standard switch</b>	<b>013469</b>	<b>013471</b>
€	N/A -	N/A -
<b>With contactless switch</b>	<b>013470</b>	<b>013472</b>
€	N/A -	N/A -

### Lina LED Lamp ➤ Swivel head ➤ Diffused lighting 25°

Flexible arm (mm)	650	1000
Luminous intensity (lm)	1680	
Illumination at 50cm (lx)	15000	
Illuminated area at 50cm (mm)	700 x 600	
Colour temperature	4500°K (neutral white)	
Rendering index Colours	IRC 95/100	
Power consumption	17 W	
Head dimensions (mm)	25 x 500	
<b>With standard switch</b>	<b>013437</b>	<b>013440</b>
€	N/A -	N/A -
<b>With dimmer switch</b>	<b>013438</b>	<b>013441</b>
€	N/A -	N/A -
<b>With contactless switch</b>	<b>013439</b>	<b>013442</b>
€	N/A -	N/A -

### Hepta LED lamp ➤ Swivel head with handle ➤ Precise 10° lighting

Flexible arm (mm)	650	1140
Luminous intensity (lm)	980	
Illumination at 50cm (lx)	60000	
Illuminated area at 50cm (mm)	120	
Colour temperature	4500°K (neutral white)	
Colour rendering index	IRC 95/100	
Power consumption	7 W	
Head dimensions (mm)	110 x 100	
<b>With standard switch</b>	<b>013409</b>	<b>013412</b>
€	N/A -	N/A -
<b>With dimmer switch</b>	<b>013410</b>	<b>013413</b>
€	N/A -	N/A -
<b>With contactless switch</b>	<b>013411</b>	<b>013414</b>
€	N/A -	N/A -

### Stands - telescopic rolling stand



- 5-star base Ø 530 mm
- Castors Ø 5 cm
- Weighted version for lamps with arms over 650 mm
- Free castors or with 2 castors with brakes

Adjustable height (mm)	600 - 1000		900 - 1300	
Type	Standard	Ballasted	Standard	Ballasted
Weight (kg)	3.7	5.5	4	5.8
<b>Cat. No. without brake</b>	<b>013474</b>	<b>013478</b>	<b>013480</b>	<b>013482</b>
€	N/A -	N/A -	N/A -	N/A -
<b>Cat. No. with brake</b>	<b>013476</b>	<b>013479</b>	<b>013481</b>	<b>013483</b>
€	N/A -	N/A -	N/A -	N/A -

### Accessory

Cat. No.	Description	€
013484	Single vice grip in black lacquered aluminium, maximum opening Ø 75 mm	N/A -
013485	Universal vice in anodised aluminium, maximum opening Ø 40 mm	N/A -
013488	White lacquered aluminium bracket for wall mounting (screws and plugs supplied)	N/A -
013492	Heavy base in white lacquered steel Ø 220 mm 1.5 kg	N/A -