

SteriMax Smart Steriliser



- Made of stainless steel with thermally insulated safety glass coating
- Special quartz inner tube, easy to clean
- No heating time required
- Infrared sensor for ignition
- Two user profiles for temperature and time settings
- Thermocontrol technology for low heat dissipation
- Warranty: 2 years

Sterilisation temperature (°C)	750 - 1000
Heating power (W)	600
Tube inn. Dim. Ø x W (mm)	16 x 112
Dimensions W x D x H (mm)	110 x 170 x 180
Weight (kg)	1.8
Power supply	220-240 V, 50/60 Hz
Protection class	IP 20
Cat. No.	788000
€	N/A -

Accessories

Cat. No.	Description	€
788001	Replacement quartz inner tube	N/A -
788002	Stainless steel 3-places tray for lateral attachment	N/A -
788003	Sterilisation rack for instruments	N/A -

"Sterilbio" Steriliser with Radiation



Sterilises loops for seeding, needles, culture tubes and small instruments effectively, destroying any organic material in 5/8 seconds at a temperature of 900 ° C.

- Built with high quality ceramic elements and inner quartz tube
- Does not require oxygen and can be used in anaerobic environments
- Eliminates aerosol problems
- Prevents bacterial contamination
- Side support included, with 4 slots for Kolle sleeves, needles, lancets, dissection forceps, etc.
- Ext. dimension: 20 x 13 x 18 cm (H x L x D)
- Ø x int. tube W: 1.4 x 15 cm
- Consumption: 110 W
- Weight: 1.5 kg

Cat. No.	Description	€
068586	"Sterilbio" Steriliser / incinerator with radiation	N/A -

Poupinel dry heat steriliser



For the rapid sterilisation of various instruments.

- AISI 304 Stainless steel interior
- Hinged lid
- Pull-out basket with grippers
- Temperature adjustable from 100 °C to 250 °C
- Equipped with a main switch, a power indicator, a timer from 0 to 120 min
- Internal dimensions (L x D x H): 25 x 12 x 6,5 cm
- External dimensions (L x D x H): 31 x 20 x 15 cm
- Power consumption 300 W / weight 4 kg

Cat. No.	Description	€
341071	DRYTHERM II Dry heat Poupinel steriliser	N/A -

UV-Box decontamination chamber



- High intensity UV lamps 254 nm
- Adjustable timer 0 - 60 min
- Stainless steel internal walls with anti-microbial surface treatment
- Anti-UV observation window
- Secure locking system with key

Ext. dim. L x D x H (mm)	387 x 521 x 483
Weight (kg)	16
Wavelength (nm)	254
Tubes	3 x 60 Watt
Power supply	220 V / 50 Hz
Cat. No.	231201
€	N/A -