

## Histological bath

Histological bath for paraffin inclusions "Termofin".

- For adjustable temperatures from 40 °C to 80 °C
- Stability ± 1 °C
- Teflon coated
- Inner tank, top and lid coated with PTFE, indelibly matt black
- With hole for temperature reading thermometer
- Control panel: main switch, temperature control thermostat, synchronised with a signal lamp
- Applications: for melting and storing paraffin in a liquid state which allows the visualisation of tissue sections

Capacity	4 litres
ø x useful height	250 x 100 mm
ø x ext. height	340 x 140 mm
Consumption	430 W
Weight	2.3 kg



Cat. No.	Description	€ Excl. VAT
068649	Histological bath for paraffin embedding	NC -

## Storage drawers

- In polystyrene
- For the storage of 165 insert moulds or 250 cassettes per drawer
- Impact resistant
- Identification labels included
- Available in packs with cassettes or inclusion moulds



Cat. No.	Description	€ Excl. VAT
040669	6 storage drawers only	NC -
040670	Pack 6 drawers + 1000 inclusion rings	NC -
040671	Pack 6 drawers + 1500 cassettes	NC -
039907	Pack 6 drawers + 1500 Histosettes I	NC -
040672	Pack 6 drawers + 1500 Histosettes II	NC -

## Paraplast-Plus Paraffin

For the inclusion of samples.

- Supplied in flake form
- Melting temperature: 56 °C
- 1 kg bag



Cat. No.	Description	€ Excl. VAT
140320	Paraplast Plus 1 kg	NC -

Find our dyes and bleaches on pages 594 and 595



## Paraffin dispenser

- Epoxy coated metal outer shell
- Internal cuvette and lid made of aluminium coated in indelible black PTFE
- Stopcock with integrated heating



Capacity (l)	4
ø x useful H (cm)	20 x 15
ø x ext. H (cm)	28 x 30
Power consumption (W)	400
Weight (kg)	5
Cat. No.	068646
€ Excl. VAT	NC -

For ambient adjustable temperatures + 5 °C to 100 °C.

- Stability ± 1.5 °C. Control panel :
- main switch, with indicator light ;
  - heating operation indicator lamp ;
  - temperature control thermostat ;
  - temperature control of the drain valve.

## Paraffin dispenser 5 l



- 5 litre paraffin capacity
- LED ignition indicator
- Backlit LCD display
- Possibility to program the start and end time of the heating cycle

Capacity	5 l Reservoir
Programmable parameters	Start and end time
Dimensions (mm)	410 x 440 x 360
Power supply	220 V, 50 Hz
Cat. No.	942904
€ Excl. VAT	NC -