

Benchtop One Touch Pipette controller 20 and 250 µl



- ▶ Semi-automatic pipettor for 96 or 384 well plates (requires adapter to be ordered separately)
- ▶ For liquid transfer from 1 to 20 µl or 5 to 250 µl depending on the model
- ▶ Intuitive control with rotary knob to set function, volume and dispensing speed
- ▶ Function: suction, dispensing, mixing, recordable programs
- ▶ Platform to accommodate a rack of tips and 2 plates, easy transfer from one plate to another
- ▶ For use with One Touch tips

▶ Technical specifications

Weight (kg)	9,5
Operating temperature	10 - 37 °C
Model 10/20 µl	
Accuracy	< 3 % (5 to 20 µl) ; < 5 % (1 to 5 µl)
Uncertainty	+/- 3 % (5 to 20 µl) ; +/- 3 % (1 to 5 µl)
Resolution	0.1 or 1 µl en using the adjustment knob
Volume range	1 µl - 20 µl
Dimensions W x L x H (cm)	21.6 x 45.7 x 43.2
Model 250 µl	
Accuracy	< 2 % (25 to 250 µl) ; < 5 % (5 to 20 µl)
Uncertainty	+/- 3 % (25 to 250 µl) ; +/- 5 % (5 to 20 µl)
Resolution	1 or 5 µl en using the adjustment knob
Volume range	5 µl - 250 µl
Dimensions W x L x H (cm)	21.6 x 45.7 x 43.2

One Touch bi-component tips on plastic rack

Cat. No.	Description	Compatible with pipettor	€ Excl.VAT the 10 x 96
010330	One Touch Tip 330 µl, non sterile	250 µl	NC -
010340	One Touch Tip 330 µl, sterile	250 µl	NC -
010350	One Touch Tip 300 µl, sterile, with filter	250 µl	NC -
010300	One Touch Tip 10/20 µl, non sterile	10/20 µl	NC -
010310	One Touch Tip 10/20 µl, sterile	10/20 µl	NC -
010320	One Touch Tip 10/20 µl, sterile, with filter	10/20 µl	NC -

Cat. No.	Description	€ Excl. VAT
014903	Pipettor Benchtop Mµlulti 10/20 µl	NC -
014901	Pipettor Benchtop Mµlulti 250 µl	NC -

Accessory

Cat. No.	Description	€ Excl. VAT
014905	Tray for use with 384-well plate	NC -

96-channel Benchtop Pipettor Liquidator 96™

RAININ
Pipetting 360°



Innovative benchtop manual pipetting system that allows 96 samples to be processed at once and provides 4 positions for continuous use.

- ▶ Flexible operation
- ▶ No programming
- ▶ Immediate results
- ▶ Unique manual pipetting system for medium to high flow applications
- ▶ Minimal space requirement, compatible with any bench top or laminar flow hood
- ▶ Compatibility with 96-well and 384-well plates

▶ Technical specifications

Volume range	5 to 200 µl, 1 µl increments
Immersion depth	Adjustable for each position
Small footprint	0.25 m ²
Weight	14 kg
Dimensions	38 x 41 x 33 cm

Cat. No.	Description	€ Excl. VAT
712821	Manual pipettor Liquidator 96™ 0.5 to 20 µl	NC -
712152	Manual pipettor Liquidator 96™ 5 to 200 µl	NC -
712149	Height adjustment rods	NC -
712154	Adapter for 384-well plate	NC -

Tips for Liquidator

Vol.	Units/box	Tips for Liquidator standard version						Tips for Liquidator Low retention version					
		Rack with removable lid		Rack with removable sterile lid		With filter, rack with removable sterile lid		Rack with removable sterile lid		With filter, rack with removable sterile lid		SpaceSaver	
		Cat.No	€ Excl. VAT/box	Cat.No	€ Excl. VAT/box	Cat.No	€ Excl. VAT/box	Cat.No	€ Excl. VAT/box	Cat.No	€ Excl. VAT/box	Cat.No	€ Excl. VAT/box
20 µl	10 x 96	17011185	NC -	712899	NC -	-	-	712364	NC -	712365	NC -	712368	NC -
200 µl	10 x 96	712146	NC -	712147	NC -	712148	NC -	712366	NC -	712367	NC -	712369	NC -