

15 AND 50 ML CENTRIFUGE TUBES

Simport® 50 ml Tubes

Volume (ml)	50	
Diameter (mm)	30	
Height (mm)	115	
Material	Polypropylene tube; sealed polyethylene screw cap	
Sterile	Yes	No
Autoclavable	Yes	
Skirt	Yes	
Graduation	Yes	
Marking area	No	
Operating temperature	-90 °C to +121 °C	
Specifications	According to CE IVD ; Tested to 95 kPa ; Chemical resistant and unbreakable	
Units/box	20 bags of 25	5 bags of 100
Cat. No. yellow cap	-	040722
Cat. No. Green cap	040721	-
€ Excl. VAT/box	NC -	NC -



Wheaton® 15 and 50 ml Tubes



Volume (ml)	15			50		
Diameter (mm)	17	17	17	29	29	29
Height (mm)	121	121	121	115	115	115
Material	Polystyrene; polyethylene cap		Polypropylene; polyethylene cap			
Sterile	Yes					
Max centrifugal speed (g)	9000	9000	9000	9500	9500	9500
Skirt	No	No	No	No	No	Yes
Graduation	Yes ; increment 0.5 ml	Yes ; increment 0.5 ml	Yes ; increment 0.5 ml	Yes ; increment 2.5 ml	Yes ; increment 2.5 ml	Yes ; increment 2.5 ml
Marking area	Yes					
Operating temperature	- 140 °C to +121 °C					
Specifications	Free of DNase, RNase and endotoxins; FDA compliant					
Units/box	10 racks of 50 tubes	10 bags of 50 tubes	10 racks of 50 tubes	20 bags of 25 tubes	20 racks of 25 tubes	20 bags of 25 tubes
Cat. No. cap	055760	055761	055762	055757	055758	055763
€ Excl. VAT/box	NC -	NC -	NC -	NC -	NC -	NC -