KLEENGUARD* G8o Chemical Protective Gloves

- ➤ Features KLEENGUARD* G80 NITRILE* gloves
- Unique NITRILE* material for excellent chemical resistance and durability
- Natural latex free to reduce the risk of type 1 allergy
- >Textured fingertips, thickness 0.38 mm
- **≻**Cotton flock lining
- > Resistant to oils, greases, acids, caustics and solvents
- >Abrasion and puncture resistance
- ➤ KLEENGUARD* G80 Neoprene/Latex Gloves Specifications
- **≻**Latex and neoprene blend
- Protection against oxidising acids, bases, alcohols, oils, greases and solvents
- ➤ Textured fingertips, thickness 0.7 mm
- ➤ Cotton flock lining





KLEENGUA	RD* G80	NITRILE	* Gloves	5			
Size	7	8	9	10	11	€ 12 pairs	
Cat. No.	038992B	038993B	038994B	038995B	038996B	NC -	
KLEENGUARD* G8o Neoprene / Latex Gloves							

KLEENGUARD* G8o Neoprene / Latex Gloves							
Size	7	8	9	10	€ 12 pairs		
Cat. No.	041428	041429	041430	041431	NC -		

KLEENGUARD* G80 NITRILE*



KLEENGUARD* G8o Neoprene / Latex

Need help? See our explanatory page on glove standards and regulations at the beginning of the Hygiene chapter and consult our technical guides at www.dulis.nl

SOL-VEX® Gloves



- ➤ Unsupported nitrile glove
- ➤ Non-suede interior finish
- ➤ Sanded exterior finish
- >2 lengths: 330 mm or 380 mm
- ➤ Colour: green
- ➤ Resistant to many solvents
- ➤ Excellent flexibility, high comfort
- >Good grip thanks to anatomical shape and sandblasted finish
- ➤ Sanitized, Actifresh: contains fungicidal and bacteriostatic agents
- Chlorine treatment to improve wet grip and make gloves easier to put on

SOL-VEX® 37-675 Gloves 330 mm

Size	6	7	8	9	10	11	€the 12 pairs
Cat. No.	678000	678001	678002	678003	678004	678005	NC -

Alphatec[®] 02-100 ex-Barrier[®] Gloves



A combination of 3 new technologies:

- a 5-layer film that offers resistance to a wide range of chemicals;
- a non-woven backing that has the same profile as the glove to ensure a snug and comfortable fit for both hand and wrist;
- a patented assembly technology that prevents the penetration of chemicals and which makes protective film and its support a single entity.
- ➤ Against irreversible risks
- ➤ Product resistant film
- ➤ Ergonomically designed to fit the hand
- Integral non-woven backing promotes moisture absorption and wicking for a cooler, more comfortable fit
- Resistant to a wide range of chemicals, for handling or cleaning hazardous materials
- ➤Thickness: 0.062 mm

Size Length	6 380 mm	7 380 mm				11 410 mm	€ the pair
Cat. No.	678067	678068	678069	678070	678071	678072	NC -