



## XENON 1950G HD barcode reader

- > Wired barcode reader
- > Superior reading performance even on damaged codes or phone screens
- > Shock resistant
- > Protection from water and dust : IP41 rating
- > Lightweight : 160 g
- > 5 year warranty

Cat. No.	Description	€
834706	Xenon 1950G HD handheld barcode scanner	NC -

### Hands-free holder

Cat. No.	Description	€
834794	Stand for XENON 1950G reader	NC -



## Label sheets for laser printers

A: width; B: height; C: printable area

Cat. No.	B x A (C) (mm)	Properties	Label/ Folios	Label/ box	€/box
<b>For centrifuge tubes, PCR, 0.5 to 0.7 ml</b>					
167871	12.7 x 19.05 mm	F N A	156	1000	NC -
167872	25.4 x 9.53 mm	F N A	175	10000	NC -
167874	9.53 x 45.72 mm (Ø 19.05)	F N A H L S	100	2500	NC -
<b>For centrifuge tubes, PCR, 1.2 to 2 ml</b>					
167873	15.24 x 41.28 mm (Ø 25.40)	F N A H L S	64	2500	NC -
167876	15.24 x 66.04 mm (Ø 25.40)	F N A H L S	64	2500	NC -
<b>For 1 to 8 ml tubes</b>					
167875	25.4 x 66.68 mm (Ø 25.40)	F N A H L S	21	1000	NC -
<b>For tube cap</b>					
167877	9.52 mm Ø	F N A	285	2500	NC -
<b>For 50 ml conical tubes, bottles, Petri dishes, tube trays</b>					
167880	36.50 x 25.4 mm	F N A	42	2500	NC -
<b>For tube trays</b>					
167881	6.35 x 47.63 mm	F A	156	10000	NC -

- > For any desktop laser printer
- > For use with Brady Workstation suite LABS

Letter	Application key
F	Freezer (- 80 °C)
N	Liquid nitrogen (- 196 °C)
A	Autoclave
H	Water baths (100 °C)
L	Ultra-thin label
R	Repositionable adhesive
S	Self-protecting label

## Safety lighting

- > Suitable for use in ATEX zones
- > Phthalate-free, non-toxic, non-flammable

### Light sticks 150 mm

- > Visible up to 1.6 km away
- > Hanging ring
- > Fold and shake to activate
- > Packaged individually

Duration	8 hrs	
Colours	Blue	White
Cat. No.	231033	231034
€	NC -	NC -

